

COMPACT HIGH-PERFORMANCE FAN HEATER

CR 130 | 950 W



- > Compact design
- > Double insulated

- > Integrated thermostat or hygrostat
- > Optional clip or screw fixing


The compact high performance fan heater prevents formation of condensation and frost and provides an evenly distributed interior air temperature in enclosures with electric/electronic components. The plastic housing provides double insulation and acts as protection against contact. The fan heater is available with integrated thermostat or pre-set hygrostat for temperature or humidity control. The CR 130 was designed as a stationary unit for wall fixing. For fixing on the bottom of the enclosure the fan heater CR 030 is recommended.



CE PUUS EN EN ROHS







TECHNICAL DATA

Heating element	high performance cartridge				
Temperature safety cut-out	with automatic reset and second-tier one shot fuse to protect against overheating in case of fan failure				
Heater body	extruded aluminium profile				
Axial fan, ball bearing	airflow 160 m 3 /h, free flow, service life 50,000 h at +25 °C (+77 °F)				
Connection	2-pole max. 2.5 mm², clamping screw with strain relief, torque 0.8 Nm max.				
Casing	plastic according to UL94 V-O, black				
Mounting	clip for 35 mm DIN rail, EN 60715 or screw fixing (M6)				
Fitting position	vertical airflow (air outlet up)				
Dimensions	182 x 168 x 99 mm				
Weight	approx. 1.5 kg				
Operating ¹ /Storage temperature	-45 to +70 °C (-49 to +158 °F)				
Operating/Storage humidity	max. 90 % RH (non-condensing)				
Protection type/Protection class	IP20 / II (double insulated)				
Note	other heating capacities from 200 W up available on request				

¹ Operating temperature of heater with integrated hygrostat: 0 to +60 °C (+32 to +140 °F)

Connection diagram <u></u>

Art. No.	Model	Operating voltage	Heating capacity	Recommended pre-fuse T (time-delay)	Setting range ²	Approvals		
13051.0-00	Fan Heater with thermostat	AC 230 V, 50/60 Hz	950 W	6.3 A	0 to +60 °C	VDE	UL File No. E234324	EAC
13051.0-02	Fan Heater with hygrostat	AC 230 V, 50/60 Hz	950 W	6.3 A	65 % RH, factory-set	VDE	UL File No. E234324	EAC
13059.9-00	Fan Heater with thermostat	AC 120 V, 50/60 Hz	950 W	10.0 A	+32 to +140 °F	-	UL File No. E234324	EAC

² Switch temperature difference 7 K (±4 K tolerance)